

| PHÖNIX-Type | Vaihinger-Type | Cat.-Sheet d | Cat.-Sheet e | Manual d | Manual e | Denomination |
|---------------|------------------|-----------------|------------------|----------------------|------------------------|---|
| 700.A1 | 16/14 CS | A001-003 | A001-002e | 416B103-1 | 416B103-1e | Glass Tube Liquid Level Gauge, CS, Glass Tube 13,5 mm, HR, PN10 |
| 700.A2 | 16/14 MS | A002-005 | A002-004e | 416B103-1 | 416B103-1e | Glass Tube Liquid Level Gauge, MS, Glass Tube 13,5 mm, HR, PN10 |
| 700.A3 | 16/14 SS | A003-003 | A003-002e | 416B103-1 | 416B103-1e | Glass Tube Liquid Level Gauge, SS, Glass Tube 13,5 mm, HR, PN10 |
| 700.A4 | 16/16 SS | A004-006 | A004-005e | 416B104-1 | 416B104-1e | Glass Tube Liquid Level Gauge, Glass holder SS, Glass Tube 13,5 mm, PN10 |
| | 68/13, 17/500 | A007-003 | A007-001e | 417B114/1 | | Drain Valves, Drain Ball Cocks |
| 700.B1 | 22/2000 | B001-007 | B001-006e | 422B107/11 | 422B107/11 | Reflection Water Level Gauge, HR, int. Side plates hinged, CS, PN40 |
| 700.B3 | 22/230 | B003-007 | B003-006e | 422B108/3 | 422B108/3 | Reflection Sight Glass Level Gauge, HR, SS, PN40 |
| 700.B5 | 17/202 | B005-008 | B005-007e | 417B104/8, 4VeL104/1 | 417B104/8e, 4VeL104/1e | Reflection Water Level Gauge, SS, hinged and rotatable glass-holder, CS, PN40 |
| 700.B6 | 17/202L | B006-008 | B006-007e | 417B104/8 | 417B104/8 | Reflection Water Level Gauge, rotatable glass-holder with pressure frame, SS, CS, PN40 |
| 700.B8 | 17/215L | B008-002 | B008-001e | 417B104/8 | 417B104/8 | Reflection Water Level Gauge, SS, rotatable glass-holder with pressure frame, obliquely, CS, PN40 |
| 700.B9 | 68/220 | B009-004 | B009-002e | 417B104/8 | 417B104/8 | Reflection Sight Glass Level Gauge, SS, hinged and rotatable glass-holder, SS, PN40 |
| | 17/206 | B020-002 | B020-002e | | | Reflection glass holder PN40 for Refl. Water LG Type 17/202, hinged and rotatable glass-holder |
| | 17/206L | B021-009 | B021-008e | | | Reflection glass holder PN40 for Refl. Water LG Type 17/202L, glass-holder with pressure frame, rotatable |
| | 17/1 | B022-003 | B022-001e | | | Shut-off Valve PN40 für Type 17/202, 17/202L |
| | 68/13, 17/500... | B023-003 | B023-001e | | | Drain Valvee, Drain Ball Cocks |
| 700.C0 | 22/230 DG-N | C100-001 | C100-002e | 422B111/2 | 422B111/2 | Transparent Sight Glass Level Gauge, HR, CS, PN40 |
| 700.C1 | 22/230 DG-S | C101-001 | C101-002e | 422B111/2 | 422B111/2 | Transparent Liquid Level Gauge, HR, SS, PN40 |
| 700.C2 | 17/230 DG | C200-002 | C200-002e | 417B109A3 | 417B109A3 | Transparent Liquid Level Gauge, SS, CS, PN40 |
| 700.C3 | 68/230 DG | C300-002 | C300-002e | 417B109A3 | 417B109A3 | Transparent Sight Glass Level Gauge, SS, SS/CS, PN40 |
| 700.C4 | 68/40 DG | C301-002 | C301-002e | 421B102/8 | 421B102/8 | Transparent Sight Glass Level Gauge, SS, SS/CS, PN63, Glass holder 95x45 |
| 700.C5 | 68/40 DG | C302-003 | C302-003e | 421B102/8 | 421B102/8 | Transparent Sight Glass Level Gauge, SS, SS/CS, PN100, Glass holder 120x36 |
| 703.C6 | 68/40 GD | C303-001 | C303-002e | 421B102/8 | 421B102/8 | Transparent Liquid Level Gauge, Mica, SS, SS/CS, PN40 |
| 703.C7 | 68/40 DF | C304-003 | C304-002e | 421B102/8 | 421B102/8 | Bicolor Liquid Level Gauge, Mica, SS, SS/CS, PN40 |
| 703.C8 | 18/30 | C400-001 | C400-002e | 418B105/6 | 418B105/6 | Refraction Liquid Level Gauge, Mica, SS, SS/CS, PN63/100 |
| 703.C9 | 18/30 | C401-002 | C401-002e | 418B105/6 | 418B105/6 | Refraction Liquid Level Gauge, Mica, Glass holder 120x36, SS, SS/CS, PN160, TV, double shut-off |
| 703.CA | 18/30 | C402-002 | C402-002e | 418B105/6 | 418B105/6 | Refraction Liquid Level Gauge, Mica, Glass holder 200x36, SS, SS/CS, PN250, TV |
| 703.CB | 18/40 | C403-001 | C403-002e | 418B101-1/6 | 418B101-1/6 | Transparent Liquid Level Gauge, Mica, SS, SS/CS, PN63/100, double shut-off |
| 703.CD | 18/40 | C404-002 | C404-002e | 418B101-1/6 | 418B101-1/6 | Transparent Liquid Level Gauge, Mica, Glass holder 120x36, SS, SS/CS, PN160, double shut-off |
| 703.CE | 18/40 | C405-001 | C405-002e | 418B101-1/6 | 418B101-1/6 | Transparent Liquid Level Gauge, Mica, Glass holder 200x36, SS, SS/CS, PN250, double shut-off |
| 760.11 | 17/1 | C500-001 | C500-001e | | | Shut-off Valve CS PN40 |
| 760.68001/2 | 68/1, 68/2 | C501-002 | C501-002e | | | Shut-off Valve CS/SS PN100/40 |
| 760.18001 | 18/1 | C502-001 | C502-001e | | | Double Shut-off Valve CS/SS PN63/100 |
| 760.18002 | 18/2 | C503-001 | C503-001e | | | Double Shut-off Valve CS/SS PN160/250 |
| | 17/9 S, Ex | C600-001 | C600-002e | 417B115A, 417B116 | 417B115Ae, 417B116e | Illumination Device, bulb 40W 230 VAC E27 for ../230 D, DG |
| | 68/9 S, Ex | C601-002 | C601-002e | 468B111, 417B109A | 468B111e, 417B109Ae | Illumination Device, bulb 40W 230 VAC E27 for ../40 D, DG |
| | 18/9 S, Ex | C602-003 | C602-003e | 418B104/2, 418B106/1 | 418B104/2e, 418B106/1e | Illumination Device, bulb 200W 230 VAC E27 for 18/40, 18/42, (PN63-250) |
| | 18/9 TV | C603-001 | C603-001e | 418B103 | 418B103e | Illumination Device, sodium vapour lamp NA 18W...NA55W |
| 700.31/32 | | | | | | Sight Glass Level Gauge PN64, for welding-in |
| 710.V010 | 75/100D2 | E001-008 | E001-005e | 475B147/2 | 475B147/2 | Magnetic Level Indicator, drain plug G1 1/4, PN10 |
| 710.V020 | 75/101D2 | E002-008 | E002-005e | 475B147/2 | 475B147/2 | Magnetic Level Indicator, drain plug G1 1/4, PN16 |
| 710.V110 | 75/100 | E003-006 | E003-004e | 475B135/7 | 475B135/7 | Magnetic Level Indicator, drain flange, PN10 |
| 710.V120 | 75/101 | E004-005 | E004-004e | 475B135/7 | 475B135/7 | Magnetic Level Indicator, drain flange, PN16, ATEX |
| 710.V140 | 75/111 | E008-008 | E008-007e | 475B135/7 | 475B135/7 | Magnetic Level Indicator, drain flange, PN40, ATEX |
| 710.V160 | 75/121 | E009-005 | E009-004e | 475B135/7 | 475B135/7e | Magnetic Level Indicator, drain flange, PN63, ATEX |
| 710.V190 | 75/141 | E010-006 | E010-005e | 475B135/7 | 475B135/7 | Magnetic Level Indicator, drain flange, PN100, ATEX |
| 710.V220 | 75/102 | E013-005 | E013-004e | 475B145/4 | 475B145/4 | Magnetic Level Indicator, drain flange, PN16, ATEX |
| 710.V240 | 75/112 | E014-005 | E014-004e | 475B145/4 | 475B145/4 | Magnetic Level Indicator, drain flange, PN40, ATEX |
| 710.V270 | 75/142-2S | E022-006 | E022-006e | 475B145/4 | 475B145/4 | Magnetic Level Indicator, drain flange, PN100, ATEX |
| 710.V280 | 75/152 S | E024-006 | E024-004e | 475B145/4 | 475B145/4 | Magnetic Level Indicator, drain flange, PN160, ATEX |
| 710.V560 | 75/122 S | E021-004 | E021-002e | 475B145/4 | 475B145/4 | Magnetic Level Indicator, drain flange, PN63, ATEX |

| PHÖNIX-Type | Vaihinger-Type | Cat.-Sheet d | Cat.-Sheet e | Manual d | Manual e | Denomination |
|----------------|---------------------|--------------|--------------|-----------------------|-------------------------|--|
| 710.V570 | 75/142-3 S | E023-004 | E023-003e | 475B145/4 | 475B145/4 | Magnetic Level Indicator, drain flange, PN100, ATEX |
| 710.V580 | 75/152-1 S | E025-005 | E025-004e | 475B145/4 | 475B145/4 | Magnetic Level Indicator, drain flange, PN160, ATEX |
| 710.V590 | 75/162 S | E026-005 | E026-004e | 475B145/4 | 475B145/4 | Magnetic Level Indicator, drain flange, PN250, ATEX |
| 710.VR40 | 75/111 RB | E011-007 | E011-005e | 475B124-1/2 | 475B124-1/2 | Magnetic Level Indicator, Drain Valve, PN40, Water regulator and limiter "Wasserstand 100" |
| 710.VR60 | 75/121 RB | E012-007 | E012-005e | 475B124-1/2 | 475B124-1/2 | Magnetic Level Indicator, Drain Valve, PN63, Water regulator and limiter "Wasserstand 100" |
| 710.102 | | | | | | Magnetic Level Indicator plastics |
| | 75/111F, 75/112F | E028-007 | E028-006e | 475B135/7, 475/B145/4 | 475B135/7e, 475/B145/4e | Magnetic Level Indicator, biggerer between float and guide tube |
| | 75/191 H, 75/191 G | E029-005 | E029-004e | 475B135/7 | 475B135/7e | Magnetic Level Indicator, inside coating Halar/rubber, PN16 |
| | 75/191 P | E030-005 | E030-004e | 475B135/7 | 475B135/7e | Magnetic Level Indicator, inside coating PTFE, PN10 |
| | 32/111 | E034-004 | E034-002e | 432B313, 416B103-1 | 432B313e, 416B103-1e | Magnetic Level Indicator, rotatable float, PN16/25, with glass tube and shut-off valve |
| 710.AVV1/2/3/4 | | | | | | Indicator type Vaihinger |
| 740.7551 | 75/51 | E041-011 | E041-009e | 475B108-10/4 | 475B108-10/4 | Magnetic Switch with inductive proximity switch (EN 60947-5-6) |
| 740.7580 | 75/80 | E041-011 | E041-009e | 475B108-9/3 | 475B108-9/3 | Magnetic Switch Reed |
| 740.7590 | 75/90 | E041-011 | E041-009e | 475B108-9/3 | 475B108-9/3 | Magnetic Switch SPDT |
| 745.110XXV | 75/F | E045-008 | E045-007e | 475B117/6 | 475B117/6 | Remote Level Indicator, Reed chain |
| 745.20H20V | 75/FV | E046-003 | E046-002e | 475B104/6 | 475B104/6 | Remote Level Indicator, Magnetostrictive |
| | PR5343 | E047-002 | E047-001e | | | Transmitter for 75/F or 85/2, programable, EEx ia IIC T1 - T6 |
| | PR5335 | E049-001 | E049-000e | | | Transmitter for 75/F bzw. 85/2, programable, EEx ia IIC T1 - T6, HART protocol |
| | FA1 | E084-005 | E084-004e | | | Ball Valve "wafer type" |
| | 23/18, 23/25, 23/1, | E085-004 | E085-003e | 432B170/1 | 432B170/1e | Shut-off valves PN16...250 |
| | 32/170, 32/178-1 | | | | | |
| | 17/200, 17/23, | E086-002 | E086-000e | see A007 | | Drain valves, Drain ball cocks |
| | 16/30, 17/311 | | | | | |
| 746.1XXX | | | | | | Float Level Gauge, Reed chain 5 / 10 / 15 mm |
| 746.20H20V | 85/FV | I004-004 | I004-003e | 485B104 | 485B104 | Float Level Gauge, Magnetostrictive |
| | PR5343 | E047-002 | E047-001e | | | Transmitter for 75/F or 85/2, programable, EEx ia IIC T1 - T6 |
| | PR5335 | E049-001 | E049-000e | | | Transmitter for 75/F bzw. 85/2, programable, EEx ia IIC T1 - T6, HART protocol |
| | Reference tube syst | I009-001 | I009-000e | | | Reference tube system |